



23 x 115 mm AIR TO AIR CANNON

Type: The two-barrel cal. 23 x 115mm air to air cannon is designed to be mounted on an aircraft fighter.

It is intended for air defense and against ground targets.



Caliber	23 mm
Rate of fire (normal conditions)	3000÷3400 rds/min
Muzzle velocity	715 ± 15 m/s
Weight	
- Cal. 23 x 115 mm cannon	49.2 kg
- Cal. 23 x 115 mm cannon with localizers	50 kg
Length	
- Cal. 23 x 115 mm cannon	1387 mm
- Cal. 23 x 115 mm cannon with localizers	1537 mm
Breadth	165 mm
Height	168 mm
- Barrel length	1000 mm
- Number of threads	10
- Threads pitch	575 mm
- Threads breadth	4.8 mm
Barrel inner diameter	
- On gaps	23.7 + 0.1 mm
- On full	23 + 0.1 mm
Triggering	electric
Cocking	manual pyro-cartridge
Guaranteed number of rounds to be fired (with the use of the pertaining set of spare parts)	minimum 4000 rounds/min (to this number there are allowed max. 200 pyrotechnic cockings from which 80 without ammunition)
Packing	1 pcs in a wooden box
Box dimensions	1373 x 345 x 319 mm
Net/Gross weight	58.5/81.5 kg